





SCALE 1/1




Specification :

Material :

1. RJ45 Jack :
 - 1-1. Housing : ABS, UL 94V-0, with Black color.
 - 1-2. Contact Bracket : PC, UL 94V-2, Transparent color.
2. RJ45 Jack Contact :
 - 2-1. Material : Phosphor Bronze with Nickel plated.
 - 2-2. Finish : 50 micro-inch Gold plated on Plug contact area.
3. RJ45 Jack Shield : Bronze with Nickel Plated.
4. PCB : FR4, UL 94V-0.

Performance :

- a. Insertion force : 30N max. (IEC 60603-7-5).
- b. Retention strength : 7.7 kg between Jack and Plug.
- c. Operating temperature : -10°C to 60°C. (ISO/IEC 11801, ANSI/TIA/EIA 568 B.2)
- d. Life(mating cycles) : 750 cycles min. (ISO/IEC 11801, IEC 60603-7-5)
- e. The Cat.5e transmission performance is in compliance with the ANSI/TIA/EIA 568 B.2 standard.

| | | | | |
|---|-----------------|-----------------------------|-------------|------------------|
|  | DSGN | Wei | 25.AUG.2010 | ITEM NO: 22 2136 |
| | CHK | Maer | 25.AUG.2010 | |
| | UNIT | M/M | APPR | Yty |
| SCALE | 1/4 | CAT.5E FULL IN-LINE COUPLER | | |
| DWG NO: | Velocity | | | |
| JE314/1 | | | | |